

Reihe 13

Fördertechnik/
Logistik

Dipl.-Ing. (FH) Jeanette Hamiga,
München

Nr. 58

Increasing Output in Transfer Lines through Adaptive Buffer Operation

Increasing Output in Transfer Lines through Adaptive Buffer Operation

Von der Fakultät Maschinenbau der Technischen Universität Dresden

zur

Erlangung des akademischen Grades

Doktoringenieur (Dr.-Ing.)

genehmigte Dissertation.

Bei: Prof. Dr.-Ing. habil. Thorsten Schmidt,

Prof. Dr. T.H.W. (Thomas) Bäck

Dipl.-Ing. (FH) Jeanette Hamiga

geboren am 12.09.1987 in Regensburg

Tag der Einreichung: 04.03.2016

Fortschritt-Berichte VDI

Reihe 13

Fördertechnik/
Logistik

Dipl.-Ing. (FH) Jeanette Hamiga,
München

Nr. 58

Increasing Output
in Transfer Lines
through Adaptive
Buffer Operation

VDI verlag

Hamiga, Jeanette

Increasing Output in Transfer Lines through Adaptive Buffer Operation

Fortschr.-Ber. VDI Reihe 13 Nr. 58. Düsseldorf: VDI Verlag 2016.

144 Seiten, 41 Bilder, 43 Tabellen.

ISBN 978-3-18-305813-6, ISSN 0178-9562,

€ 52,00/VDI-Mitgliederpreis € 46,80.

Keywords: Transfer Lines – Simulation – Multi-Objective-Optimization – Evolution Strategies – Automotive Production – Manufacturing System – Assembly – Buffer – Adaptive Buffer Operation – Decoupling Effect

This thesis is intended for engineers and scientists in the field of production. It deals with the goal of increasing output in (serial) transfer lines and simultaneously decreasing labor costs without need of change to the structure of the production system. For this the method adaptive buffer operation is developed, implemented and validated. Adaptive buffer operation proposes a different way of operating buffers, improving the decoupling effect of buffers. The buffers are filled to certain target fill levels at fixed moments (times of the day). Apart from the target fill levels further parameters, e.g. moments of intervention or the intervention frequency, are identified. To find out how to operate the buffers and which parameter combinations work best, a simulation-based optimization method is proposed. This method is split into the evaluative methodology, here simulation, and the generative technique of evolution strategies, solving the multi-objective optimization problem. Proof of performance is demonstrated while applying the method to a simulation model of an assembly of a German automotive plant.

Bibliographische Information der Deutschen Bibliothek

Die Deutsche Bibliothek verzeichnet diese Publikation in der Deutschen Nationalbibliographie; detaillierte bibliographische Daten sind im Internet unter <http://dnb.ddb.de> abrufbar.

Bibliographic information published by the Deutsche Bibliothek

(German National Library)

The Deutsche Bibliothek lists this publication in the Deutsche Nationalbibliographie (German National Bibliography); detailed bibliographic data is available via Internet at <http://dnb.ddb.de>.

© VDI Verlag GmbH · Düsseldorf 2016

Alle Rechte, auch das des auszugsweisen Nachdruckes, der auszugsweisen oder vollständigen Wiedergabe (Fotokopie, Mikrokopie), der Speicherung in Datenverarbeitungsanlagen, im Internet und das der Übersetzung, vorbehalten.

Als Manuskript gedruckt. Printed in Germany.

ISSN 0178-9562

ISBN 978-3-18-305813-6

Acknowledgements

Diese Arbeit entstand im Rahmen des Doktorandenprogrammes ProMotion der BMW AG in Zusammenarbeit mit dem Institut für Technische Logistik und Arbeitssysteme der Fakultät Maschinenwesen an der Technischen Universität Dresden.

Ich bedanke mich herzlich bei Prof. Dr.-Ing. habil. Thorsten Schmidt, meinem Doktorvater und Inhaber der Professur für Technische Logistik, für die Übernahme der Betreuung und für das mir entgegengebrachte Vertrauen. Mein besonderer Dank gilt Herrn Prof. Dr. Thomas Bäck von der Natural Computing Research Group am Leiden Institute of Advanced Computer Science (LIACS) für die Übernahme des Koreferats als auch für die anregenden Diskussionen. Die daraus hervorgehenden Impulse haben die Arbeit stets bereichert. Herrn apl. Prof. Dr.-Ing. habil. Michael Völker danke ich für die Unterstützung und Begleitung während der Entstehung dieser Arbeit.

Darüber hinaus bedanke ich mich insbesondere bei Jan Knau, meinem Betreuer, sowie bei allen Kollegen der BMW AG, die mich während meiner Zeit als Doktorandin unterstützt haben. Besonders danken möchte ich hier Markus Ganser für die zahlreichen fachlichen Diskussionen sowie für seine Übernahme der Rolle des Advocatus Diaboli, ohne die diese Dissertation in dieser Form nicht möglich gewesen wäre.

Auch den Kollegen der divis intelligent solutions GmbH, insbesondere Herrn Christophe Foussette und Dr.-Ing. Peter Krause danke ich sehr für die hervorragende Zusammenarbeit, die konstruktive Kritik und Diskussion.

Mein tiefster Dank gilt meiner Familie und meinen Freunden, die mich auf meinem Weg unterstützt haben.

München, März 2016

Jeanette Hamiga

Index

Nomenclature and acronyms	VIII
Notations	X
Symbols	XI
1 Introduction	1
1.1 Background and motivation of research	1
1.2 General objective.....	3
1.3 Structure of this dissertation	5
2 Buffer management in manufacturing systems	7
2.1 Fundamentals in manufacturing	7
2.2 Evaluative solution methodology in manufacturing systems optimization.....	10
2.2.1 Simulation	10
2.2.2 Decomposition	11
2.2.3 Design of Experiments	12
2.3 Generative solution methodology	13
2.3.1 Fundamentals in optimization	13
2.3.2 Optimization methods.....	15
2.3.3 Evolutionary Algorithms	17
2.4 Requirements of a solution method to increase output	25
2.4.1 System-oriented requirements to the solution method	25
2.4.2 Application-oriented requirements.....	26

2.4.3	Summary of requirements.....	28
2.5	Analysis of relevant approaches	28
2.5.1	Buffer allocation problem	29
2.5.2	Optimal production control: the hedging point policy	32
2.6	Assessment of existing approaches and need for further research.....	36
3	Method design for increased output in assembly	39
3.1	General outline of method for increasing output.....	39
3.2	Assumptions and notations.....	41
3.3	Adaptive buffer operation: method description and its parameters.....	42
3.3.1	Buffer filling policy	43
3.3.2	Target fill level.....	44
3.3.3	Moments of intervention	46
3.3.4	Variable intervention parameters.....	48
3.3.5	Conclusion and identified intervention parameters.....	49
3.4	Buffer filling algorithms.....	50
3.4.1	Simplified example: two machine transfer line	50
3.4.2	$Mn + 1$ machine transfer line.....	51
3.4.3	Calculation of time to stop before end of production	55
3.5	Simulation-based method used for optimization	56
3.5.1	Performance indicators to be monitored	56
3.5.2	Optimization concept.....	58
3.5.3	Evolutionary Algorithms used for search of solutions	59
3.6	Implementation of the simulation-based solution method	62
4	Application of method.....	64
4.1	Model building	64
4.1.1	Conceptual model.....	65

4.1.2	Data collection and processing	67
4.1.3	Verification and validation (V&V) of model	71
4.1.4	Number of replications and run-length	75
4.2	Experiments.....	77
4.2.1	Single-objective optimization: minimize manufacturing cost per unit.....	77
4.2.2	Single-objective optimization: maximize output.....	85
4.2.3	Multi-objective optimization.....	86
4.2.4	Further experimentation.....	89
4.2.5	Conclusion of results and findings	93
4.3	Concluding assessment and discussion	95
5	Summary and outlook.....	97
A	Results single-objective optimization	100
B	Results multi-objective optimization	103
C	Results further experiments	111
D	Validation of simulation	114
	References	118

Nomenclature and acronyms

ADDX	Accelerated DDX
AG	Aktiengesellschaft
BMW	Bayerische Motoren Werke
CVA	ClearVu Analytics, software used for optimization
DDX	Dallery-David-Xie
DLL	Dynamic Link Library
DoE	Design of Experiments
DR	Derandomized
EHPP	environmental HPP
FIFO	First In First Out
HPP	hedging point policy
min	minimum
min	minute
NSGA	Non-dominated Sorting Genetic Algorithm
PHPP	prioritized HPP
R	Range (of the target buffer level)
RSM	Response Surface Methodology
s	second
SDHPP	state depended HPP
T	Target buffer level

tol	tolerated
VW	Volkswagen
V&V	Verification and Validation
WIP	work-in-progress
xml	Extensible Markup Language

Notations

x	vector x
$u \otimes v$	element-wise multiplication of vectors $u, v \in \mathbb{R}^n$ $u \otimes v = w$ where $w \in \mathbb{R}^n$ and $w_i = u_i \cdot v_i$ for $i \in \{1, \dots, n\}$
x^T	transposition of vector x
x_i	indexed component of a vector $x = (x_1, \dots, x_n)^T \in \mathbb{R}^n$

Symbols

η	availability of system in %
α	significance level
<i>Optimization</i>	
k	index for constraints $k = 1, 2, \dots, r$
l	index for constraints $l = 1, 2, \dots, m$
K	total number of inequality constraint functions
L	total number of equality constraint functions
V	feasible set of the original problem
M	total number of objective functions
m	index for objective functions
n	number of parents to be optimized
\mathbf{x}	offspring vector
i	index number of individual / solution
j	index number of individual / solution
<i>Evolutionary Algorithms</i>	
t	continuous generation index $t = 0, 1, 2, \dots$
P_t	population at generation t
Q_t	offspring population at generation t
p	individual of population P_t
q	individual of population Q_t

Ψ	finite set of strategy parameters
λ	number of offspring
μ	number of parents
γ	number of generations
ρ	number of parents participating in creating offspring
κ	maximum age of an individual
<i>DR2</i>	
ϕ_i	fitness of individual i
\mathbf{z}_i	random vector of the multivariate normal distribution
δ_{scal}	local step size
δ	global step size
sel	index of selected offspring
β	exponent for global step size
β_{scal}	exponent for local step size
ζ	vector accumulating selected variation information over generations
c	factor controlling weight of last generation in contrast to current generation

Evolutionary Multi-objective Optimization

r_i	non-domination rank of individual / solution i
d_i	local crowding distance of individual / solution i
$<_c$	crowded comparison operator

NSGA-II

N	size of population P
R_t	population formed by joining P_t and Q_t

\mathcal{F}_i	different Pareto fronts, with $i = 1, 2, \dots$ etc.
<i>Developed method</i>	
$level_{target}(B_i)$	target level of buffer B_i
$level_{current}(B_i)$	current level of buffer B_i
δ_i	Difference between current and target buffer level of buffer B_i
$units(M_i)$	number of units machine M_i has to produce
$units_{tmp}(M_i)$	number of temporary units machine M_i has to produce
$units(max)$	Number of units the machine, with the maximum number of $units(M_i)$ has to produce
$M_i(cycles)$	Number of cycles machine M_i has to stop before machine with $units(max)$
$cycles(M_i)$	Number of cycle times machine M_i has to stop before the last machine stops or production is ceased in general
$range(B_i)$	Indicates the range within which the buffer fill level can lie for the case of the tolerated buffer fill level as target
$level_{min}(B_i)$	Minimum target fill level (tolerated buffer fill level as target)
$level_{max}(B_i)$	Maximum target fill level (tolerated buffer fill level as target)
$\delta_{i_{min}}$	Difference between current and minimum target buffer level of buffer B_i (tolerated buffer fill level as target)
$\delta_{i_{max}}$	Difference between current and maximum target buffer level of buffer B_i (tolerated buffer fill level as target)
$count(\delta_{i_{min}} < 0)$	Indicates how many buffers are below minimum fill level
$count(\delta_{i_{max}} > 0)$	Indicates how many buffers exceed maximum fill level

